


CHIVAS




natural 01



mocca 13



cinnamon 97



clay 84



brown 15



cognac 28



grey 65



liver 10




brandy 127



slate 87




graphite 60



wenge 192



jungle 207



forest 162

Chivas - Article passport

Natural leather aspect article with a full hand feel.

Available from stock in a wider range of contemporary and commercial colours.

Product characteristics

| | |
|----------------------|---|
| Product group | microsued woven |
| Applications | sofa's, beds, chairs with fitted and loose fitting upholstery |
| Composition faceside | |
| 1 0 0 % P E | S |
| Composition backside | |
| 1 0 0 % P E | S |
| Statistic Code | 54076990 |
| Bonding | fleece |
| Dyeing method | piecedyed |
| Available colours | 14 |

Durability specifications

| Test | Test Specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ 430/4:2016-01 | | Norm DIN EN 14 465:2006-09 |
|-------------------------------------|--|-------------------------|--------|------------|-----|--------------------------|----------------------|----------------------------|
| | | | | DRY | WET | DGM | DGM+ | |
| Abrasion Resistance - yarn breakage | DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-05 | CTL | cycles | 72.000 | | min. 8.000 | min. 16.000 | C |
| Pilling | DIN EN ISO 12945-2:2000-11, 2000 cycles | CTL | grade | 4 | | min. 3-4 | min. 4 | B |
| Colour fastness to light | DIN EN ISO 105-B02:2014-11, Process 3, exposure level 5 | CTL | grade | 4-5 | | min. 4 | min. 5 | B-C |
| | | | | 4-5 | | min. 4 | min. 5 | B-C |
| | | | | 4-5 | | min. 4 | min. 5 | B-C |
| Colour fastness to rubbing | DIN EN ISO 105-X12:2016-11 | CTL | grade | 5 | 4-5 | dry: 4, wet: 3 | dry: min 4, wet: 3-4 | A/A |
| | | | | 4-5 | 4-5 | dry: 4, wet: 3 | dry: min 4, wet: 3-4 | A/A |
| | | | | 4-5 | 3-4 | dry: 4, wet: 3 | dry: min 4, wet: 3-4 | A/A |
| Ignitability | BS 5852 part 1 (1979) from The Furniture and Furnishings (Fire) (Safety) Regulations: 1988 No. 1324, Schedule 4 part 1. Ignition source: cigarette | CTL | | passed | | | | |

Processing specifications

| Minimum workable width in centimeters | ± 138 | | | | | | | |
|---|--|-------------------------|--------|------------|------|--------------------------|----------|----------------------------|
| Roll length in meters | ± 30 | | | | | | | |
| Material weight in grams per linear meter | ± 600 | | | | | | | |
| Test | Test Specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ 430/4:2016-01 | | Norm DIN EN 14 465:2006-09 |
| | | | | WARP | WEFT | DGM | DGM+ | |
| Tensile strength | DIN EN ISO 13934-1:2013-08 | CTL | Newton | 1.332 | 375 | min. 350 | min. 400 | A/C |
| Tear growth resistance | DIN EN ISO 13937-3:2000-06 | CTL | Newton | 101,2 | 58,0 | min. 25 | min. 30 | A/A |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07, Load 180 N | CTL | mm | 2,0 | 2,0 | max. 5 | max. 4 | A/A |
| Delamination | DIN 53530:1981-02 | CTL | Newton | 25,5 | 21,8 | n/a | n/a | n/a |
| Chemical substances | REACH | Centexbel | | passed | | | | |

Cleaning specifications

| Test | Test Specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ 430/4:2016-01 | | Norm DIN EN 14 465:2006-09 |
|--|---|-------------------------|------|------------|---------|--------------------------|------|----------------------------|
| | | | | WARP | WEFT | DGM | DGM+ | |
| Dimensional change for washing 30 degrees Celsius / air drying | DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08 | CTL | % | +/- 0,0 | +/- 0,0 | n/a | n/a | A/A |



We recommend to immediately place the cover back to the piece of furniture slightly damp after washing. Please note that washing has a negative effect on the damp- and dirt prevention treatment; by washing the treatment will disappear faster. Dirt and Damp prevention treatment applied.



Textaafoam
creativity in fabrics

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle The
Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl