



Member



OEKO-TEX®
CONFIDENCE IN TEXTILES



FABRAA[®]
fabrics with a conscience



Member

This textile is made from 100% sustainable material and offers the best value for money, fitting every style all year round. Member is a 100% RPET woven fabric and is part of the www.wovenbottles.com collection.

A textile which has an elegant structure, with a rather soft handfeel, both the face side and the backing are made from plastic bottles. For more information on this sustainable production process, please visit our website www.fabraa.com.

Member has been woven on an air jet loom and has a trendy and wide colourline, suitable for all kinds of upholstery. Washable at 30 degrees Celsius (machine).

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.

Fabraa Upholstery fabrics with a conscience. We make sustainable choices easy by offering a wide range of high-quality, affordable upholstery fabrics with consideration for the conditions throughout the supply chain.

Composition

/ faceside 100%RPET
/ backside 100%RPET
/ flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



ashgrey 40



azure 144



beige 05



blush 92



bronze 116



cacao 83



carmine 36



cognac 28



denim 153



desert 109



forest 162



onyx 169

Please note: colours may vary according to your screen settings.



sage 203



slate 87



taupe 12



thyme 206



wood 108



zinc 167



Please note: colours may vary according to your screen settings.

Member - Article passport

A 100% sustainable article with an elegant structure and rather soft handfeel.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

| | |
|----------------------|---|
| Productgroup | flatweave |
| Applications | sofa's, beds, chairs with fitted and loose fitting upholstery |
| Composition faceside | 100%RPET |
| Composition backside | 100%RPET |
| Bonding | non-woven |
| Statistic code | 54075200 |
| Dyeing method | piece dyed |
| Available colours | 18 |
| Packaging | transparent plastic |

Durability specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
|-------------------------------------|---|--|--------|------------|----------------|-------------------------|--------------------|----------------------------|
| | | | | Dry | Wet | DGM | DGM+ | |
| Abrasion resistance - yarn breakage | DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03 | CTL | cycles | 55.000 | | min. 12.000 | min. 16.000 | A |
| Pilling | DIN EN ISO 12945-2:2000-11. 2000 cycles | CTL | grade | 4-5 | | min. 3-4 | min. 4 | A |
| Colour fastness to light | DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5 | | | | | | | |
| | light colours | CTL | grade | 4-5 | | min. 4 | min.5 | B-C |
| | middle colours | CTL | grade | 4-5 | | min. 4 | min.5 | B-C |
| Colour fastness to rubbing | DIN EN ISO 105-X12:2016-11 | | | | | | | |
| | light colours | CTL | grade | 4-5 | 4-5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A |
| | middle colours | CTL | grade | 5 | 4-5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A |
| dark colours | CTL | grade | 4-5 | 4-5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A | |
| | Ignitability (cigarette test) | BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette | CTL | passed | | | | |



Processingspecifications

| Minimum workable width in centimeters | ± 143 | | | | | | | |
|---|--|-------------------------|--------|------------|------|-------------------------|----------|----------------------------|
| Roll length in meters | ± 40 | | | | | | | |
| Material weight in grams per linear meter | ± 450 | | | | | | | |
| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
| | | | | Warp | Weft | DGM | DGM+ | |
| Tensile strength | DIN EN ISO 13934-1:2013-08 | CTL | Newton | 770 | 489 | min. 350 | min. 400 | A/B |
| Tear growth resistance | DIN EN ISO 13937-3:2000-06 | CTL | Newton | 95,2 | 89,6 | min. 25 | min. 30 | A/A |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07. Load 180 N | CTL | mm | 3,5 | 4,5 | max. 5 | max. 4 | A/B |
| Delamination | DIN 53530:1981-02 | CTL | Newton | 34,2 | 26,2 | n/a | n/a | n/a |
| Chemical substances | REACH | Centexbel | | passed | | | | |
| | Oeko-Tex, product class II | Centexbel | | certified | | | | |

Cleaning specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RALGZ430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
|--|---|-------------------------|------|------------|------|-------------------------|------|----------------------------|
| | | | | Warp | Weft | DGM | DGM+ | |
| Dimensional change for washing 30 degrees celcius / air drying | DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08 | CTL | % | 0,0 | 0,0 | n/a | n/a | A/A |

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.



Textafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@fabraa.com
www.fabraa.com