

# TUNE

General Product Specification	
Product group	Artificial leather polyurethane (PU)
Composition faceside	100%PU
Composition backing	60%PES 40%CO
Coating	
Material Weight	602 g/lm
Tariff No.	39211310
Minimum usable width	138 cm
Roll length	30 mtr
Number of colors	12



Product Specific Properties:
<ul style="list-style-type: none"> <li>- soft grip</li> <li>- shiny aspect</li> <li>- stain friendly, cleanable with a damp cloth (cotton)</li> <li>- moisture-repellent</li> <li>- meets the Standard BS5852 Cigarette&amp;Match</li> </ul>

**Information about the Productgroup:**

This is produced by means of a liquid substance, in this case polyurethane, which is applied to a backing. A leather-like texture can be created by printing / stamping on the fabric. This article is strong and has a natural feel and aspect to it. The material is less detrimental to the environment and not harmful to health, since this product contains no harmful plasticizers (REACH).

Test specifications:	
Abrasion resistance <i>ENISO 12947 1 &amp; 2</i>	> <b>200000</b> cycles till yarnbreakage Martindale
Pilling resistance <i>ENISO 12945-2</i>	class <b>n/a</b> 2000 Rubs
Lightfastness <i>ENISO 105 B02</i>	Light colors <b>4-5</b> Middle colors <b>4-5</b> Dark colors <b>4-5</b>
Tensile (breaking str.) <i>ENISO 13934-1</i>	Warp <b>700</b> Newton Weft <b>400</b> Newton
Tear strength <i>ENISO 13937-3</i>	Warp <b>45,0</b> Newton Weft <b>31,0</b> Newton
Seam slippage <i>ENISO 13936 2</i>	Warp <b>2,2</b> mm Weft <b>2,7</b> mm
Fastness to rubbing <i>ENISO 105 X12</i>	class <b>4-5</b> Wet class <b>4-5</b> Dry

Test specifications:	
Yarn dyed	
Piece dyed	✓
Damp- prevented	✓
Dirt-prevented	✓
Flame resistance	
Cigarette test:	BS 5852 (1979) ✓
Match test:	BS 5852 (1979) ✓

