





















## Earth

This piece dyed knitted velvet is strong and machinewashable at 30 degrees Celsius\*. A sustainable textile which is part of our www.wovenbottles.com collection.

The pile provides a comfortable softness and creates a light shiny and elegant look.

A velvet which is made in a sustainable way from 100% RPET bottles. This luxurious upholstery fabric is durable and very easy to clean and maintain.

Earth is suitable for all types of upholstery and we supply this velvet in a wide range of trendy, modern and commercial colours.

- Please note that no fluor-carbon treatment has been used for this quality, due to the production and dyeing method it is automatically damp & dirt prevented, stain resistant and easy to clean & maintain.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.
   Please note that during washing the damp- and dirt prevented treatment will disappear faster.
- Dirt and damp prevention treatment applied.

Fabraa Upholstery fabrics with a conscience. We make sustainable choices easy by offering a wide range of high-qualty, affordable upholstery fabrics with consideration for the conditions throughout the supply chain.

Composition

/ faceside 100%RPET / backside n/a / knitted velvet

Suitable for



Please note: colours may vary according to your screen settings.



## Earth - Article passport

Knitted velvet made from 100% RPET bottles with a light shiny and elegant look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics					
Productgroup	knitted velvet				
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery				
Composition faceside	100%RPET				
Composition backside	n/a				
Bonding / Coating	n/a				
Statistic code	60053900				
Dyeing method	niece dved				

Durahility	enocifications

Available colours Packaging

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09		
				Dry	Wet	DGM	DGM+			
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 20.000	min. 40.000	А		
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	А		
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5					•				
	light colours	CTL	grade		5	min. 4	min.5	В		
	middle colours	CTL	grade	5		min. 4	min.5	В		
	dark colours	CTL	grade			min. 4	min.5	В		
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11	DIN EN ISO 105-X12:2016-11								
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
	middle colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
	dark colours	CTL	grade	4	4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/B		
gnitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		pas	ssed					

Processingspecifications
--------------------------

Material weight in grams per linear meter	± 620			
Roll length in meters	± 35			
Minimum workable width in centimeters	± 138			
3-1				

Material weight in grams per linear meter	± 620							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	631	982	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	46,7	60,7	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,1	2,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		pas	sed			
	Oeko-Tex, product class II	Centexbel		certified				

## Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	0,0	n/a	n/a	A/A













boxes

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.
  Please note that during washing the damp- and dirt prevented treatment will disappear faster.
  Dirt and damp prevention treatment applied.















