

Oasis

















Oasis

Introducing a nice, thick, luxury flatwoven article for the Textaafoam Timeless collection, by the name: Oasis.

The Timeless collection represents all our creative essentials and consists out of fabrics that have the very best value for money and suit every style all year round.

Oasis has a strong multicoloured aspect, yet the woven structure is more elegant and will combine perfectly with some plain Textaafoam qualities, like Challenger, Juke or Seven. Because of the elegant weave Oasis is an ideal article for loose- and tight-fitting upholstery. Sofa's, chairs, footstools and beds will look great in this nice new quality.

On top of that the rough and tough look combines wonderfully with Oasis' luxurious feel. The soft and comfortable touch is the result of the yarns used in combination with a needle punch coating. Oasis is yarn dyed and thus very stable in it's colour consistency.

During use, a certain hairiness or woolines can appear, kindly note that this can be taken away with a pilling machine and has no further influence on the durability of this quality.

Oasis is machine-washable at 30 degrees Celsius.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoamoriginals Established in 1970,this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer □s needs everytime. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside n/a / flatweave

Suitable for



Please note: colours may vary according to your screen settings.



Oasis - Article passport

Article with a multicoloured aspect, rough construction and woolly and full grip.

Available from stock in a wide range of contemporary and commercial colours.

Product	characteristics
---------	-----------------

r roduct criaracteristics		
Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	n/a	
Coating	needle punch	
Statistic code	54076990	
Dyeing method	yarn dyed	
Available colours	19	
Packaging	transparent plastic	

Durability specifications

Test		Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09
					Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage		DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100	0.000	min. 12.000	min. 16.000	А
Pilling		DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	В
Colour fastness to light		DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
		light colours	CTL	grade	5		min. 4	min.5	В
		middle colours	CTL	grade	5		min. 4	min.5	В
		dark colours	CTL	grade	5		min. 4	min.5	В
Colour fastness to rubbing		DIN EN ISO 105-X12:2016-11							
		light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
		middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
		dark colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
gnitability (cigarette test)		BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: digarette	CTL		pas	ssed			

Processingspecifications

.					
Minimum workable width in centimeters	± 140				
Roll length in meters	± 30				
Material weight in grams per linear meter	± 667				
·		 	 -	 	

Material weight in grams per linear meter	± 667							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.200	909	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	213,2	208,8	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,0	2,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RALGZ430/4:2019-01		Norm DIN EN 14 465:2006-09	
				Warp	Weft	DGM	DGM+		
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,8	-0,4	n/a	n/a	A/A	











- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.















creativity in fabrics

Textaafoam b.v. La Défense 11 | 5026 SC Tilburg

P.O. Box 12 | 5050 AA Goirle The Netherlands

ilburg rle T +31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl