

# NORONEN

## Fondo



Fondo-100



Fondo-101



Fondo-103



Fondo-104



Fondo-105



Fondo-110



Fondo-118



Fondo-201



Fondo-203



# NORONEN

## Fondo



Fondo-215



Fondo-326



Fondo-402



Fondo-503



Fondo-800



Fondo-803



Fondo-805



Fondo-808

# Fondo

## Product information



Total composition	97% PES, 3% VSC
Composition faceside	97% PES, 3% VSC
Composition backing	Not applicable
Water repellent finish	Yes
Useful fabric width	142 +/- 2%cms
Average roll length	30-50 m
Fabric weight	330 g/m2
HS code	0

### Important fabric characteristics

- ☐ Upholstery fabrics are sensitive to direct influx of ultraviolet light (sun-or halogen light) and may discolour over time.
- ☐ Intense and dark colours are more sensitive to discoloration caused by ultraviolet light.
- ☐ Intense and dark colours have a lower rub fastness grade.
- ☐ Wet fabrics have a lower rub fastness grade.
- ☐ Dye lot differences may occur.
- ☐ Pilling caused by clotting of upholstery fabric fibres with dust or other fibres may occur.
- ☐ It is recommended to maintain the humidity level of the room to guarantee the elasticity of the fibres and avoid build-up of static electricity.
- ☐ Light and plain fabrics are more sensitive to staining.
- ☐ Direct contact with chemical solvents (e.g. in glue sprays) can deteriorate fabric properties.
- ☐ In contact with sharp objects scissors, cutters, nails ...) surface damage or pulled loops are unavoidable.
- ☐ Do not expose upholstery fabric to direct heat sources.

### Fabric care instructions



# Fondo

## Product information



### Technical specifications

<u>Martindale</u> 10.000 45.000		EN ISO 12947-2:2016
pilling according to Martindale method		
	500 rubs (pile worn off > 5mm <sup>2</sup> )	
	1.000 rubs (yarn breakage)	
	2.000 rubs	
	5.000 rubs	
<u>seam slippage</u>		EN ISO 13936-2:2004
4,2 mm	warp	
3,3 mm	weft	
<u>tear strength</u>		EN ISO 13937-3:2000
53,8 Nabs	warp	
71,8 Nabs	weft	
<u>tensile strength</u>		EN ISO 13934-1:2013
617 N	warp	
529 N	weft	
<u>light fastness</u>		EN ISO 105-B02:2014
note 4-5	dark colours	
note 4-5	light colours	
<u>rub fastness - wet</u>		EN ISO 105-X12:2002
note 3-4	dark colours	
note 4-5	light colours	
<u>rub fastness - dry</u>		EN ISO 105-X12: 2002
note 3-4	dark colours	
note 4-5	light colours	
<u>flame retardancy level</u>		
PASS	cigarette	DIN EN 1021-1:2014

