NORONEN

Home









Home

Home is a genuine style icon in our comfort collection. Softness, volume and elegance are just some of the characteristics for this type of qualities.

We have succeeded to create a fabric with the atmosphere of home and the care free maintenance, to enjoy your furniture to the fullest. This slightly shiny soft chenille textile* has a subtle and elegant look and is a true treat to the touch. It creates a very natural appearance on each type of model.

The fabric is a flat-woven quality of 100% polyester with a light back coating and C0 easyclean finish. The piece dyed colour range is developed in a full range of natural tones and warm deep colourshades that represent the latest interior fashion trends.

Thanks to the type of yarns and finish, it is also in the www.picobello-fabrics.com collection. Easy to clean, easy to maintain and even machine-washable at 30 degrees Celsius*. Each type of furniture will look and stay fabulous in any colour.

There's no place (or fabric) like Home.

- Please note that due to chenille yarns, shading and seat depression are possible.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside n/a / chenille flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



Please note: colours may vary according to your screen settings.



thyme 206

Please note: colours may vary according to your screen settings.

		//	
ome - Article passport			
A soft fine structured chenille fabric with easy clean finis	shing.		
Available from stock in a wide range of contemporary ar	d commercial colours.		
Product characteristics			
Productgroup	chenille flatweave		
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery		
Composition faceside	100%PES		
Composition backside	n/a		
Coating	transparent		
Statistic code	55159130		
Dyeing method	piece dyed		
Available colours	22		
Packaging	bubble wrap	-	

est		Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09		
					Dry	Wet	DGM	DGM+			
Abrasion resistance - yarn breakage		DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 12.000	min. 16.000	В		
Pilling		DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	В		
Colour fastness to light		DIN EN ISO 105-B02:2014-11. Process 3, exposure level 5 Ught colours									
		middle colours	СТ	grade	4	-	min. 4	min.5	B-C		
		dark colours	L	grade	5		min. 4	min.5	B-C		
		DIN EN ISO 105-X12:2016-11	СТ	grade	4-		min. 4	min.5	B-C		
Colour fastness to rubbing		light colours	L CT		5						
			CTL	grade	5 5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
		middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
		dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A		
gnitability (cigarette test)		BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed			·			

Minimum workable width in centimeters	± 138							
Roll length in meters	± 35							
Material weight in grams per linear meter	± 580							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.840	685	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	104,2	37,4	min. 25	min. 30	A/B
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07.	CTL	mm	1,5	1,5	max. 5	max. 4	A/A
	Load 180 N			n/a	n/a		n/a	
Detamination	DIN 53530:1981-02	CIL	Newton			n/a		n/a
Chemical substances	REACH	Centexbel		ра	ssed			
	Oeko-Tex, product class II	Centexbel		cer	tified	1		

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,2	0,0	n/a	n/a	A/A
P 🐨 🗟 🔿 🖄	- We recommend to wash the cover in	side out and immediate	ely place the cov	er back to the piec	e of furniture, slightl	ly damp, after wash	ng.	



Textaafoam^b creativity in fabrics

Textaafoam b.v. La Défense 11 | 5026 SC Tilburg P.O. Box 12 | 5050 AA Goirle The Netherlands T +31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl (M)

CTL® GmbH

OEKO 150 211274 Control CEN TEX BEL