

# NORONEN

## Scene



OEKO-TEX®  
CONFIDENCE IN TEXTILES



**Textaafoam**  | Timeless  
creativity in fabrics



# Scene

A polyester flatwoven textile which is in the Textaafoam Timeless Collection. This collection represents all of our creative essentials.

Upholstery fabrics that offer the best value for money and suit every style all year round. With Scene we developed an elegant quality, with a light melange aspect. Laminated with a non-woven backing, it feels comfortable and voluminous.

Scene consist of a polyester yarn, woven on an air jet loom. Piece dyed and treated with a damp and dirt finish, so perfect suitable for intensive use. Available in a wide, trendy and modern colour line and also washable at 30 degrees (machine wash)\*.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.
- Please note that during washing the damp- and dirt prevented treatment will disappear faster.
- Dirt and damp prevention treatment applied.

***Textaafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

## Composition

/ faceside 100%PES  
/ backside 100%PES  
/ flatweave

## Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery





ashgrey 40



beige 05



blush 92



bronze 116



denim 153




espresso 123



gold 132



graphite 66




liver 10



niagara 158



onyx 169



pearl 106

Please note: colours may vary according to your screen settings.



plumb 168



raspberry 163




shell 196



slate 87



taupe 12



thyme 206

Please note: colours may vary according to your screen settings.

## Scene - Article passport


An elegant quality, with a light melange aspect that feels comfortable and voluminous.

Available from stock in a wide range of contemporary and commercial colours.

## Product characteristics

Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	100%PES	
Bonding	non-woven	
Statistic code	54075200	
Dyeing method	piece dyed	
Available colours	18	
Packaging	transparent plastic	






## Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	50.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

## Processing specifications

Minimum workable width in centimeters	± 143							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 435							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.506	570	min. 350	min. 400	A/B
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	96,4	51,7	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,7	3,9	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	22,4	14,1	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

## Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-1,0	0,0	n/a	n/a	A/A
    				<ul style="list-style-type: none"><li>- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.</li><li>- Please note that during washing the damp- and dirt prevented treatment will disappear faster.</li><li>- Dirt and damp prevention treatment applied.</li></ul>				

Oeko-TEX®  
certification in textiles



**Textaafoam**  
creativity in fabrics

Textaafoam b.v.  
La Défense 11 | 5026 SC Tilburg  
P.O. Box 12 | 5050 AA Goirle  
The Netherlands

T +31(0)13 534 5934  
F +31(0)13 534 7586  
E [info@textaafoam.nl](mailto:info@textaafoam.nl)  
[www.textaafoam.nl](http://www.textaafoam.nl)

mei 2022