

Board



















Board

This fine woven melange-coloured textile is in the Textaafoam Timeless Collection. This collection features all our creative essentials. Fabrics that offer the best value for money and suit every style all year round.

Yarn dyed, woven on a dolby loom and still one of Textaafoam best-sellers through the years. Strong, suitable for all types of furniture, tight or loose fitted or even buttoned furniture, they all look great with Board. Due to the needle punch coating, it gives a full, woolly and comfortable handfeel. Also perfect to combine with other Textaafoam originals. Board is machine-washable at 30 degrees Celsius and available from stock in an enormous wide, modern and commercial colour line of 49 Colours.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside n/a / flatweave



Please note: colours may vary according to your screen settings.



Please note: colours may vary according to your screen settings.



Please note: colours may vary according to your screen settings.



turquoise 44 winered 39 yellow pastel 195



A fine woven melange-coloured article with a full, woolly and comfortable handf	eel.							
Available from stock in a wide range of contemporary and commercial colours.								
-								
Product characteristics	-	-	_	-	-	-	_	
Productgroup	flation and a faile banks about the	Γ						
Applications	flatweave sofa's, beds, chairs with							
Applications	fitted and loose fitting upholstery							
Composition faceside	100%PES							
Composition backside	n/a							
Coating	needle punch							
Statistic code	54075300							
Dyeing method	yarn dyed							
	49							
Available colours	transparent plastic							
Packaging								
Durability specifications								
Test	Test specification	Executed by	Unit	Testr	esult	Norm RAL GZ	430/4:2019-01	Norm DIN EN 14
		laboratory:					1	465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	32.	000	min. 12.000	min. 16.000	В
- NIII	DIN EN ISO 12947-2:2017-03 DIN EN ISO 12945-2:2000-11.							_
Pilling	2000 cycles	CTL	grade		4	min. 3-4	min. 4	В
Colour fastness to light	DIN EN ISO 105-BO2:2014-11.					1	l	
	Process 3, exposure level 5							
	light colours	CTL	grade	4	-5	min. 4	min.5	В
	middle colours	CTL	grade	4	-5	min. 4	min.5	В
	dark colours	CTL	grade		4	min. 4	min.5	С
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11					ı	l	
Colour lastics to labsing	light colours							
		CTL	grade	5	5	dry: 4,	dry: > 4,	A/A
						wet: 3	wet: 3-4	
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4,	dry: > 4,	A/A
	dark colours	0.2	grade			wet: 3	wet: 3-4	,,,,
Ignitability (cigarette test)	BS 5852 part 1 (1979) from	CTL		pas	sed			
	The Furniture and Furnishing (Fire) (Safety) regulations:							
	1988 No. 1324. Schedule 4 part 1							
	Ignition source 0: cigarette							
Parameter and Continue								
Processing specifications	_							
Minimum workable width in centimeters	± 138							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 399		1			1		
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
		,.		Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.020	1.612	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	89,8	157,7	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07.	CTL	mm	3,8	3,2	max. 5	max. 4	A/A
- Delamination	Load 180 N	CTL	Newton	n/a	n/a		n/a	n/a
- Chemical substances	DIN 53530:1981-02	Centextel				n/a		1,75
	REACH	Centexbel		passed				
	Oeko-Tex, product class II			certified				
Cleaning specifications								
Test	Test specification	Executed by Unit		Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
		laboratory:		Warp	Weft	DGM	DGM+	405:2006-09
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04,	CTL	%	2,0	0,0	n/a	n/a	A/A
and the figure of the same and the sa	DIN EN ISO 6330:2013-02,		/0	2,0	3,0	.1/ 0	, 0	. 475
	DIN EN ISO 3759:2011-08	<u> </u>	<u> </u>					
	- We recommend to wash the cover in	iside out and immedia	tely place the co	over back to the pied	e of furniture, slig	htly damp, after was	ning.	
(P) (M) (M) (M)								
	1							















Board - Article passport

Textaafoam b.v. La Défense 11 | 5026 SC Tilburg P.O. Box 12 | 5050 AA Goirle The Netherlands